

SC-1022-20 VOLUNTEER



The **SC-1022**
VOLUNTEER

from

CARSON
SIRENS

***“The SC-1022, “a small siren with big results”
in the palm of your hand.*”**

The Carson **SC-1022 Volunteer** Hand-held Mechanical Tone Siren for those who need to clear traffic in a big way. This small compact siren offers the standard tones of wail, yelp, manual and the new Carson mechanical tone along with dip switch programmability of the European HiLo/Two-tone sound as optional substitutes. This gives you full coverage for any emergency situation. Expect big results with this small siren. The completely enclosed rubberized face gives you a smooth front panel with everything right at your finger tips. This hand-held remote control head with light controls for emergency situations is easily operated and ideal when you want it out of your way and not in use.

This small 100-watt siren with big results is the **SC-1022 Volunteer** Hand Held Mechanical tone siren that offers all the same reliable performance, rugged and durability along with consistent quality that comes with all the Carson Siren line.

- **Mechanical Tone:** This sirens deep and gutsy mechanical tone allows you to sound just like a fire truck clearing traffic. This siren will set you apart from the rest.
- **Lighted Pushbutton Controls:** Two lighted pushbutton switches for controlling auxiliary or emergency lighting.
- **Horn Ring Cycler 2:** Allow the operator the capability to run the siren tones from the vehicle horn ring or other external switching for hands free tone selection during pursuit or rescue situations.
- **Control Head Mounting Bracket Included:** A “holster” that allows mounting to dash or console for easy access.

***The SC-1000 Series offers
“a small siren with big results”.***

CARSON
SIRENS

5451 North Rural Street - Indianapolis, IN 46220
1.888.577.6877 or 317.257.3191 - Fax 317.254.2667 - www.carsonsirens.com

SC-1022-20 VOLUNTEER

Specifications

Siren	
Input Voltage	9 - 16 VDC (negative ground)
Input Current	8 Amps @14 VDC
Standby Current	Less than 50 mA (enabled), less than 5mA standby
Output Power	105W RMS Max (@15 VDC - single 100W speaker)
Siren Frequency	700Hz - 1500Hz (Mechanical 700 Hz - 1600Hz; Two-Tone & Horn = 435 & 585Hz)
Tones/Cycle Rates	Horn = 109 CPS, Mechanical = 5 CPM, Wail = 13 CPM, Yelp = 190 CPM, Phaser = 15 CPS, Two-Tone = 60 CPM
High Voltage Protection	16 - 18 VDC output ceases, resumes at normal level
Short Circuit Current	50 Amps Min. from supply circuit
Operation Temperature	-15F to 140F
Controls	Six membrane Pushbuttons, auxiliary input programmable for +/- activation. 8-position DIP switch option selector.
Siren Connections	Removable 10-Pos Terminal Block: (2) Power, (2) Speaker, Auxiliary and Enable inputs, (2) light control outputs. RJ-12 jack for hand control with built-in cable.
Light Control	
Voltage	9 - 16 VDC (negative ground)
Controls	Two pushbuttons
Auxiliary Switch Current	5 Amps max per circuit, 5 Amps max total
Light Connections	Two light control outputs
General	
Size	Control Head: 1-7/8" Wide, 1" Deep, 4" High Amplifier: 6" Wide, 4-1/4" Deep, 1-7/8" High
Shipping Weight	2 Lbs
Ratings Met	Class A Sound Level, California Title 13, KKK

Features

- Remote hand held unit with pushbutton controls
- Compact 100-watt electronic siren amplifier with 5 amps of light control
- Two illuminated pushbuttons for light control
- Six pushbutton switches for Mechanical, Wail, Yelp, Phaser, Manual, and Air Horn with optional European HiLo/Two Tone siren tone
- DIP switch programmable tones
- Horn Ring Cyler (HRC2) for hands free siren tone control
- Short circuit, high voltage and reverse polarity protection systems
- Control Head bracket (Holster) included
- Small amplifier size with flange mounting
- No hassle 5-year limited warranty

	<i>SC-1022</i> VOLUNTEER	Federal Signal Mini MS4000U	Whelen Alpha 12M/12R	Code 3 PSE Compact 3900 Remote	Signal Vehicle Products (SVP)SS651	Able 2 Products Sho-Me 30.3104/ 30.2106/ 30.2109	Galls SK123
Mechanical Tone	YES		YES				
Light Control Outputs	YES						
Auxiliary Input & Horn Ring Capabilities	YES		YES				
Flexible DIP Switch Programmability	YES		YES				
5-Year Warranty	YES						YES



WARNING Sound Hazard - Sound level from siren speaker (>120dBA @ 10 feet) may cause hearing damage. Do not operate siren without adequate hearing protection for you and anyone in immediate vicinity. (Ref. OSHA 1910.95 for occupational noise exposure guidelines)

CARSON
SIRENS

5451 North Rural Street - Indianapolis, IN 46220
1.888.577.6877 or 317.257.3191 - Fax 317.254.2667 - www.carsonsirens.com