



from



## "The Remote Siren That Clears the Way"

The **SC-1012 Volunteer** 100-watt remote siren with light controls was designed with the volunteer firefighter in mind offering complete versatility. This unit gives you flexibility in the placement of the remote switch panel and amplifier. The remote switch panel features two 3-position rocker switches to select between wail, yelp, manual, and mechanical tone. A momentary rocker switch for air-horn and phaser with the European HiLo/two-tone sound as an optional substitute. The siren also features the Horn Ring Cycler (HRC2) function that enables the driver hands-free control of the siren by cycling through the tones with the vehicles horn. Two lighted rocker switches are also included for controlling emergency lights.

The siren is installed with a detachable connector for the power, speaker and remote switch panel. The siren tones may be changed or disarmed using a Dip switch. The light switches are capable of switching up to 20 amps. This siren is designed to work with a 100-watt speaker and ensures you the strength to get you where you need to go and be heard like one of the big fire trucks. The remote panel may be mounted with holes in the top or bottom. As with all Carson Sirens products, the **SC-1012 Volunteer** is backed by a no-hassle 5-year limited warranty.

The **SC-1012 Volunteer** Remote Siren offers the reliable performance, and rugged durability with consistent quality that comes with every Carson Siren.

- **Mechanical Tone:** This sirens deep and gutsy mechanical tone allows you to sound just like a fire truck clearing traffic. This siren will set you apart from the rest.
- Lighted Rocker Switches: Two lighted rocker switches for controlling auxiliary lighting.
- Horn Ring Cycler 2: Allow the operator the capability to run the siren tones from the vehicle horn ring or other external switching for hands free tone selection during pursuit or rescue situations.

The SC-1000 Series offers "a small siren with big results".



## **Specifications**

## Siren

Input Voltage 9 - 16 VDC (negative ground)

Input Current 8 Amps @14 VDC

Less than 10mA Standby Current

**Output Power** 105W RMS Max (@15 VDC - single 100W speaker)

700Hz - 1500Hz (Mechanical 700 Hz - 1600Hz; Siren Frequency Two-Tone & Horn = 435 & 585Hz)

Horn = 109 CPS, Mechanical = 5 CPM, Wail = Tones/Cycle Rates

13 CPM, Yelp = 190 CPM, Phaser = 15 CPS,

Two-Tone = 60 CPM

High Voltage Protection 16 - 18 VDC output ceases, resumes at normal level

**Short Circuit Current** 50 Amps Min. from supply circuit

-15F to 140F Operation Temperature

> Two 3 Position rocker switches, 2 position rocker momentary Horn and Phaser, auxiliary input Controls for +/- activation, 8 position DIP switch

options selector

Removable 12-Pos Terminal Block: (2) Power, (2) Speak-Siren Connections

er, Auxiliary inputs, (6) Icontrol switch inputs.

**Light Control** 

Voltage 9 - 16 VDC (negative ground)

Controls Two lighted rocker switches in control panel.

**Auxiliary Switch Current** 20 Amps max per switch (externally fused)

General

Control Head 4-1/2" Wide, 1-3/4" Deep, 2" High Size Amplifier: 6" Wide, 4-1/4" Deep, 1-7/8" High

Shipping Weight

Ratings Met Class A Sound Level, California Title 13, KKK

## **Features**

- Compact 100-watt electronic siren amplifier with 20 amps of light control
- Two illuminated rockers for light control
- Siren Wail, Yelp, Phaser, Manual, Air Horn, and Mechanical tone with optional European HiLo/Two Tone siren tone
- Rocker switch siren function control with momentary rocker switch override
- DIP switch programmable tones
- Horn Ring Cycler (HRC2) for hands free siren tone control
- Amplifier and light controls fused separately and externally
- Short circuit, high voltage and reverse polarity protection systems
- Detachable wiring connector
- Small amplifier size with flange mounting
- No hassle 5-year limited warranty

	SC-1012 VOLUNTEER	Federal Signal Mini MS4000U	Whelen Alpha 12M/12R	Code 3 PSE Compact 3900 Remote	Signal Vehicle Products (SVP)SS651	Able 2 Products Sho-Me 30.3104/ 30.2106/ 30.2109	Galls SK123
Mechanical Tone	YES		YES				
Light Control Out- puts	YES						
Auxiliary Input & Horn Ring Capabilities	YES		YES				
Flexible DIP Switch Programmability	YES		YES				
5-Year Warranty	YES						YES



Sound Hazard - Sound level from siren speaker (>120dBA @ 10 feet) may cause hearing damage. Do not operate siren without adequate hearing protection for you and anyone in immediate vicinity. (Ref. OSHA 1910.95 for occupational noise exposure guidelines)

